

Technical data sheet

Hollow core anchor Easy

Item no. 3498774



Hollow core anchor "Easy" for mounting in prestressed hollow concrete slabs. When the screw or the nut is tightened, the cone is released from the anchor sleeve and pulled into it. This makes the anchor expand in the hollow space, thereby creating firm lock. The hollow core anchor can also be used when the expansion area is not located in the cavity.

The fastening of the component can be done with standard screws and threaded rods.

St	Steel
G	Electrogalvanised

Product description

Additional product text, instruction	General type approval Z-21.1-1785 granted by the German Institute for civil engineering (DIBt), Berlin, including permissible loads when exposed to fire up to a fire resistance duration of 120 minutes.
--------------------------------------	---

Master data

Item no.	3498774
Type	Easy M10
Description 1	Hollow core anchor Easy
Dimension	M10
Material	Steel
Material symbol	St
Surface	Electrogalvanised
Surface to DIN	DIN EN 12329
Surface symbol	G
Smallest sales unit (VG)	25,00 Piece
Weight	3,32 kg/100 pc.


Technical data sheet

Hollow core anchor Easy

Item no. 3498774



Technical data



Length	53,00 mm
Dimension L	53,00 mm
Drill hole depth	60,00 mm
Drill hole diameter	16,00 mm
Thread	M10
Thread metric	10,00
With thread	☒
With bolts	☐