Technical data sheet

Quick pipe, light grey

Item no. 2153912



Quick Pipe combines the advantages of cable duct and installation pipe in an intelligent system. This system allows tidy and safe surface-mounted installation of all kinds of cables on walls and ceilings. Quick pipe is available in four metric sizes: M16, M20, M25 and M32. The stock length is 2 m.
The system is VDE-tested and achieves a protection rating of IP44. The Quick Pipe can be used in the temperature range between -25 and +60 °C and is resistant against impact energy of 5 J.
The fittings are a component part of the system. The smallest shipped quantity is one shipping box.

CE IP 44 M

PVC Polyvinylchloride

Master data

Item no.	2153912
Type	2953 M20 LGR
Description 1	Quick pipe
Dimension	M20
Colour	Light grey
RAL number	7035
Material	Polyvinylchloride
Material symbol	PVC
Smallest sales unit (VG)	40,00 m
Weight	11,50 kg/100 m

Technical data



Length	2.000,00 mm
Dimension C	10 mm
Dimension D	20,00 mm
Dimension M	17
Dimension t	1,50 mm
Surface-mounted	☑
Flame-resistant version	☐
type	Moulded, self-closing cover
Concrete installation	☑
Size	M20
Halogen-free	☐
Installation on wood	☑
Installation under the ground	☐
Installation outdoors	☐
Machines and system installation	☑
With sleeve	☐
Temperature range	-25-+60 °C
Underfloor installation (screed)	☐

Technical data sheet

Quick pipe, light grey

Item no. 2153912

Technical data

Concealed	□

Classification for electrical pipe standards

Classification for electrical pipe standards