

Technical data sheet

Set made of Quick clip and Quick pipe

Item no. 2154536



Convenient set consisting of Quick clip and Quick pipe.

The Quick pipe combines the advantages of cable duct and installation pipe into an intelligent system. This system allows tidy and safe surface-mounted installation of all kinds of cables on walls and ceilings. Quick pipe is available in four metric sizes: M16, M20, M25 and M32 and the stock length is 2 m.

The system is VDE-tested and achieves a protection rating of IP44. The Quick pipe can be used in the temperature range from -25 to +60 °C and is resistant to an impact energy of 5 J.




PVC Polyvinylchloride

Master data

Item no.	2154536
Type	2954 M25 LGR
Description 1	Quick-Pipe set
Description 2	Quick trunking + Quick clip
Dimension	M25
Colour	Light grey
RAL number	7035
Material	Polyvinylchloride
Material symbol	PVC
Smallest sales unit (VG)	1,00 Piece
Weight	517,00 kg/100 pc.

Technical data



Dimension M	21,8
Dimension t	1,60 mm
Surface-mounted	☒
Flame-resistant version	☐
Concrete installation	☒
Size	M25
Halogen-free	☐
Installation on wood	☒
Installation under the ground	☐
Installation outdoors	☐
Machines and system installation	☒
With sleeve	☐
Temperature range	-25-+60 °C
Quick pipe	30,00 m
Quick clip	96,00 pc.

Technical data sheet

Set made of Quick clip and Quick pipe

Item no. 2154536



Technical data	
Set consisting of	30 m Quick pipe and 96x OBO Quick clip
Underfloor installation (screed)	☐
Concealed	☐

Classification for electrical pipe standards
Classification for electrical pipe standards