



Valves | Single Check Valves | **Check Valves, Single**

Models F-908-W, W-910-B, F-910-B, KG-900-W, KW-900-W...

Product Specification

Model No	Description	Valve Size		Rated Working Pressure		Remarks
		in	(mm)	psi	(kPa)	
F-908-W	Swing Check Valve, Flanged Ends	4, 6, 8, 12	(100, 150, 200, 300)	175	(1205)	b
W-910-B	Silent Check Valve, Wafer Type	2, 2 1/2, 3, 4, 5, 6, 8, 10	(50, 65, 80, 100, 125, 150, 200, 250)	200	(1380)	a, e
W-910-B-LF W-910-W-LF	Silent Check Valve, Wafer Type	2, 2 1/2, 3, 4, 5, 6, 8, 10	(50, 65, 80, 100, 125, 150, 200, 250)	200	(1380)	c, d, e
F-910-B	Silent Check Valve, Flanged Ends	2 1/2, 3, 4, 5, 6, 8, 10, 12	(65, 80, 100, 125, 150, 200, 250, 300)	200	(1380)	a, e
F-910-B-LF F-910-W-LF	Silent Check Valve, Globe Ends	2 1/2, 3, 4, 5, 6, 8, 10, 12	(65, 80, 100, 125, 150, 200, 250, 300)	200	(1380)	c, d, e



Model No	Description	Valve Size		Rated Working Pressure		Remarks
		in	(mm)	psi	(kPa)	
KG-900-W-LF	Swing Check Valve Dual Disc-Grooved Ends	2 1/2, 3, 4, 5, 6, 8, 10, 12	(65, 80, 100, 125, 150, 200, 250, 300)	250	(1725)	b, c, e
KW-900-W-LF	Swing Check Valve, Dual Disc-Wafer Type	2 1/2, 3, 4, 5, 6, 8, 10, 12	(65, 80, 100, 125, 150, 200, 250, 300)	250	(1725)	b, c, e
KW-900-W-LF	Swing Check Valve, Dual Disc-Wafer Type	14, 16	(350, 400)	200	(1380)	b, d, e

Remarks:

- a. Metal Seat
- b. Resilient Seat.
- c. Available with a lead-free Silicon-Bronze disc and seat alloy. Designated by an "LF" Suffix.
- d. Available with resilient or metal seat.
- e. No removable covers.

Details

Approval Standard : FM 1210 - Swing Check Valves

Certification Type : FM Approved

Class of Work : 1210 - Single Check Valves

Listing Country : United States of America

Company

NIBCO Inc

1516 Middlebury St, Elkhart, Indiana 46516

United States of America

<http://nibco.com>

