



Valves | Anti-Water Hammer Check Valves | **Check Valves, Anti-Water Hammer**

KW-990-E-LF

Resilient Seated Valves. The rated working pressure of the valves listed below is 300 psi (2065 kPa).

Product Specification

Model No	Valve Size		Flow Rate		Friction Loss	
	in	(mm)	gal/min	(dm ³ /min)	psi	(kPa)
KW-990-E-LF	2	(50)	210	(795)	9.1	(63)
KW-990-E-LF	2 1/2	(65)	300	(1135)	5.5	(38)
KW-990-E-LF	3	(80)	460	(1740)	6.6	(45)
KW-990-E-LF	4	(100)	795	(3010)	9.3	(64)
KW-990-E-LF	5	(125)	1245	(4710)	7.7	(53)
KW-990-E-LF	6	(150)	1800	(6815)	6.2	(43)
KW-990-E-LF	8	(200)	3120	(11810)	3.0	(21)



Model No	Valve Size		Flow Rate		Friction Loss	
	in	(mm)	gal/min	(dm ³ /min)	psi	(kPa)
KW-990-E-LF	10	(250)	4915	(18605)	3.0	(21)
KW-990-E-LF	12	(300)	7050	(26685)	3.8	(26)
KW-990-E-LF	14	(350)	8450	(31985)	3.2	(22)
KW-990-E-LF	16	(400)	11000	(41635)	4.1	(28)

Details

Certification Type : FM Approved

Class of Work : 1230 - Anti-Wtr Hammer Ck Valves

Approval Standard : FM 1230 - Anti-Water Hammer Check Valves

Listing Country : United States of America

Category : Check Valves, Anti-Water Hammer

Company

NIBCO Inc

1516 Middlebury St, Elkhart, Indiana 46516

United States of America

<http://nibco.com>