

Specyfikacje



Eaton 149164

Eaton xEnergy Basic LV systems Low voltage switchgear. Surface-mount service distribution board with three-point turn-lock, mounting side panel, W = 1200 mm, H = 1260 mm

General specifications

PRODUCT NAME	Eaton xEnergy Basic small distribution board
CATALOG NUMBER	149164
EAN	4015081455102
PRODUCT LENGTH/DEPTH	280 mm
PRODUCT HEIGHT	1275 mm
PRODUCT WIDTH	1215 mm
PRODUCT WEIGHT	46.1 kg
COMPLIANCES	RoHS conform
MODEL CODE	BP-O-1200/12-PSN



Delivery program

TYPE	Basic device
APPLICATION	Indoor (installation site) Mounting side wall
COLOR	Gray

Technical data - mechanical

CLOSURE TYPE	Other
SURFACE FINISHING	With powder coating
ENCLOSURE MATERIAL	Steel

Light gray (RAL 7035)

WIDTH IN NUMBER OF MODULAR SPACINGS	57
MOUNTING METHOD	Surface mounted (plaster) Surface mounting
MATERIAL	Sheet steel
NUMBER OF ROWS	7
BUILT-IN DEPTH	280 mm
BUILT-IN HEIGHT	1275 mm
BUILT-IN WIDTH	1215 mm
COVER/DOOR MODEL	Closed
COVER/DOOR TYPE	Door Three-point turn-lock Double

Temperature-rise verification as per IEC 60890

HEAT DISS. AMBIENT 35°C DELTA T: 20°C WALL MOUNT MIDDLE ENCL. TOP (IEC 60890)	175 W
HEAT DISS. AMBIENT 35°C DELTA T: 35°C WALL MOUNT MIDDLE ENCL. TOP (IEC 60890)	351 W
HEAT DISS. AMBIENT 35°C DELTA T: 20°C WALL MOUNT INDIVID. ENCL. TOP (IEC 60890)	187 W
HEAT DISS. AMBIENT 35°C DELTA T: 20°C WALL MOUNT STARTING ENCL. TOP (IEC 60890)	180 W
HEAT DISS. AMBIENT 35°C DELTA T: 35°C WALL MOUNT INDIVID. ENCL. TOP (IEC 60890)	375 W
HEAT DISS. AMBIENT 35°C DELTA T: 35°C WALL MOUNT STARTING ENCL. TOP (IEC 60890)	361 W

Design verification as per IEC/EN 61439

10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Not relevant to indoor installations.
10.2.5 LIFTING	Does not apply to enclosures without lifting aids.
10.2.6 MECHANICAL IMPACT	IK07
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	IP30
10.4 CLEARANCES AND CREEPAGE DISTANCES	Is the panel builder's responsibility.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	< 0.1 Ω; meets the product standard's requirements.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Is the panel builder's responsibility.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-	Ui = 440 V AC

FREQUENCY ELECTRIC STRENGTH	
10.9.3 IMPULSE WITHSTAND VOLTAGE	4 kV
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Does not apply to metal enclosures.
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility.
10.13 MECHANICAL FUNCTION	Meets the product standard's requirements.

Additional information	
FEATURES	EMC-version
FUNCTIONS	Basic device Extension possible
RAL-NUMBER	7035

Zasoby	
BROSZURY	eaton-xenergy-basic-light-brochure-br014024-en-us.pdf
DEKLARACJE ZGODNOŚCI	DA-DC-03_xEnergy_Basic_BP
DWG	eaton-low-voltage-switch-gear-dimensions-1230dim-434.eps
INFORMACJE HANDLOWE	eaton-f3a-flange-flyer-fl019005en-en-us.pdf
KATALOGI	eaton-distribution-boards-xenergy-basic-catalog-ca014010en-en-us.pdf
MCAD MODEL	eaton-cadenas-side_view-bp_0_msw_19_s_side.pra eaton-cadenas-path-media_assets-assemblies-bp_0_msw_19_asmtpl.prj eaton-cadenas-front_view-bp_0_msw_19_v_front.pra DA-CS-bp_0_msw_19 DA-CD-bp_0_msw_19

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATA:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Irlandia
Eaton.com

© 2025 Eaton. Wszelkie
prawa zastrzeżone.

Eaton jest zarejestrowanym
znakiem towarowym.

Wszystkie inne znaki towarowe są
własnością odpowiednich firm.

Follow us on social media to get the latest
product and support information.

